



- [Products](#)
- [Services](#)
- [Industries](#)
- [Customer Support](#)

[Home](#) | [About Us](#) | [Contact Us](#)



Welcome! [FREE Online Services](#) | [Premier Services](#) | [Profile/Preferences](#)

➤ [Rubber Fabrication Solutions Home Page](#)

Silicone Rubber

- [Applications and Markets](#)
- [Basic Silicone Rubber Information](#)
- [Physical and Chemical Properties](#)
- [Processing Methods](#)
- [Product Types](#)
- [Services](#)

Tools

- [Find Products/Data Sheets](#)
- [Product Q&A](#)
- [My Rubber Compound Request](#)
- [Find a Distributor](#)
- [Newsletter Archive](#)
- [Français, Italiano, and Español Help](#)

Contact Us

- [Dow Corning Rubber Locations](#)
- [Ask an Expert](#)

Technical Library

- [Glossary](#)
- [Technical Articles](#)
- [Selection Guides](#)

Rubber Physical and Chemical Properties

[Rubber Home](#) > [Physical and Chemical Properties](#) > [Temperature Resistance Properties](#) > Thermal Expansion Conductivity and Specific Heat

Thermal Expansion


The coefficient of volumetric thermal expansion for all *Silastic*® silicone rubber products is in the range of 5.9 to 44/°C. The linear coefficient of thermal expansion is roughly one-third of the volumetric coefficient of thermal expansion. The linear coefficient of thermal expansion can be used to calculate the total linear thermal expansion of a rubber part over a temperature range.

Example: If the volumetric coefficient of thermal expansion is $5.9 \times 10^{-4}/^{\circ}\text{C}$ and the temperature span is 150°C, the linear expansion of a part one-inch long would be ... $5.9 \times 10^{-4}/^{\circ}\text{C} \times 150^{\circ}\text{C} \times 1 \text{ in.} = 0.0295 \text{ in.}$

Thermal Conductivity


Values usually range from 0.330 to $0.515 \times 10^{-3} \text{ g-cal/sec/cm}^2/\text{cm}/^{\circ}\text{C}$.

Thermal Conductivity, K



Specific Heat

The specific heat of *Silastic* silicone rubber ranges from 0.28 to 0.35 cal/gr/°C. Generally, the higher hardness rubbers (60 or more durometer points) are at the low end of this range and lower hardness rubbers are at the high end.

Specific Heat of *Silastic*® Liquid Silicone Rubber

Do you want to learn more?

- [Find Products/Data Sheets](#)
- [Customize your own Rubber Compound](#)
- [Find your application](#)
- [Ask an Expert](#)
- [Learn about our Mechanical Testing services](#)

[back to Rubber Physical and Chemical Properties](#)

[www.dowcorning.com.cn](#) [www.dowcorning.co.kr](#) [www.dcts.co.jp](#) [www.molykote.com](#) [More global websites...](#)

Using this website means you understand our [Privacy Statement](#) and agree to our [Terms & Conditions](#).

©2000 - 2004 Dow Corning Corporation. All rights reserved. Dow Corning is a registered trademark of Dow Corning Corporation. We help you invent the future is a trademark of Dow Corning Corporation.